

VERSION	CHANGE
07.31.11	Original version
08.03.11	<p>Page 1 - Under Suggested Yarn, alternate yarn requirements have been revised:</p> <p style="padding-left: 40px;">821 (937, 1025, 1102, 1217, 1299, 1391, 1491, 1587, 1707) yds / 751 (857, 937, 1008, 1113, 1188, 1272, 1363, 1451, 1561) m</p>
09.15.11	<p>Page 1 - Under Suggested Yarn, yardage has been revised:</p> <p style="padding-left: 40px;">737 (821, 937, 1025, 1102, 1217, 1299, 1391, 1491, 1587, 1707) yds / 681 (751, 857, 937, 1008, 1113, 1188, 1272, 1363, 1451, 1561) m Catherine Lowe Couture Yarns <i>CL I #6B</i> (68% Extrafine Merino, 32% Silk) in Black Violet.</p> <p style="padding-left: 40px;"><i>Catherine Lowe Couture yarns are sold by yardage, not by weight or by the skein.</i></p>
12.22.11	<p>Stitch counts for size 42 <math>\frac{3}{4}</math>" / 108.5 cm (5th size) have been revised for the Front:</p> <p>On page 2, middle column, in the 3rd paragraph under Front, the 3rd line should begin: "Work 13 (14, 16, 20, <b>26</b>, 24, 25, 24, 25, 30) sts, pm...."</p> <p>On page 2, right column, the 5th paragraph should begin: "Move cable panel one st to the left every 8 (6, 6, 6, <b>6</b>, 6, 4, 4, 4, 4) rows 4 (8, 9, 6, <b>11</b>, 1, 16, 11, 10, 10) times, then every 6 (4, 4, 4, <b>0</b>, 4, 2, 2, 2, 2) rows 4 (3, 2, 7, <b>0</b>, 15, 2, 12, 15, 15) times...."</p>
06.19.13	<p>Page 4 - In the left column, the last line should end: "...ending with a <b>WS</b> row."</p> <p>Page 4 - In the middle column, the first line should begin: "Next row (<b>RS</b>):".</p>
09.16.13	<p>Page 2 - In the middle column, the third paragraph under Front has been changed:</p> <p>Continue as established until Hem Cable Chart is complete. On your last RS row, mark cable panel as follows: Work <b>14 (14, 14, 24, 26, 24, 25, 24, 24, 25)</b> sts, pm, work 18 sts, pm, work to end. On your next row, evenly decrease <b>11 (16, 20, 14, 19, 22, 23, 26, 27, 35)</b> sts from the section before the first marker and <b>4 (3, 0, 9, 5, 5, 5, 5, 4, 1)</b> st(s) from the section after the second marker to accommodate the</p>

difference in gauge from the Hem Cable to St st: 72 (80, 86, 92, 100,  
106, 112, 120, 126, 134) sts rem.